



ACHILLE

Pulsante Antivandalo con braille.
Vandal resistant push button with braille.



FUNZIONI PRINCIPALI

- Corpo: pulsante in zama e nylon.
- Collarini: zama, (cromo o oro, nichel perlato, oro perlato, canna di fucile/rutenio).
- Parte mobile: polycarbonato con superficie esterna rivestita in acciaio inox AISI 304 (possibilità di trattamento in PVD color oro o nero); cifra o decorazione in rilievo brunita e braille.
- Montaggio: il pulsante viene inserito frontalmente in uno scasso Ø 32,2 e fissato tramite una ghiera filettata.
- Spessore piastra: da 0,7 mm a 5 mm.
- Contatti: 1 micro switch o 2 micro switches.
- Cablaggio: connettori a vite o sistemi precablati (AMP, JST o minispox).
- Illuminazione: Led 12V o 24V DC 30mA.
- Corsa pulsante: 1,2 mm.
- Vita media: 2.000.000 di attivazioni.
- Grado di protezione: IP51 con molla metallica e IP54 con molla siliconica e o-ring.

MAIN FEATURES

- Body: zamak and nylon push button.
- Bezels: zama (chrome or gold, pearled nickel, pearled gold, anthracite).
- Pressel: polycarbonate with stainless steel AISI 304 or gold/black pvd coated finishes; raised legend(s) and Braille.
- Mounting: the button is put into the cutout (Ø 32,2) from the front and fixed by threaded ring.
- Faceplate Thickness: 0,7 mm to 5 mm.
- Contacts: 1 micro switch or 2 micro switches.
- Wiring: PIN or pre-wired connectors (AMP, JST or minispox).
- Illumination: Led 12V o 24V DC 30mA.
- Stroke: 1,2 mm.
- Avg. life: 2.000.000 activations.
- Degree of protection: IP51 with metal spring/IP54 with silicone spring and o-ring.



ACHILLE TLM-X

Pulsante Achille con sensore touch-less.
Achille push button with touch-less sensor.



- Sensore touch-less: con emettitore IR integrato (850nm) ed emettitore laser.
- Distanza d'attivazione: 3 cm max.
- Contatti: 1 micro switch.
- Cablaggio: connettori MINISPOX (5268).
- Illuminazione: bicolore (corona illuminata a 2 colori).

- Touchless sensor: with integrated IR emitter (850nm) and laser emitter.
- Activation distance: 3 cm max.
- Contacts: 1 micro switch.
- Wiring: MINISPOX connectors (5268).
- Lightings: Bicolor (halo with 2 lightings).

ALTERNATIVE / ALTERNATIVES



ACHILLE_TD: Achille tornito base con parte mobile in polycarbonato con superficie esterna rivestita in acciaio inox AISI 304 tornito (possibilità di trattamento in PVD color oro o nero); nessuna cifra presente. Disponibile con targhetta braille. / Turned Achille with pressel in polycarbonate with stainless steel AISI 304 or gold/black pvd coated finishes; no legend(s). Braille available with separate plate.

ACHILLE_AZ: Achille effetto unghia con parte mobile in zama (cromo o oro, nichel perlato, oro perlato, canna di fucile). / Achille with nail shaped; pressel in zama (chrome or gold, pearled nickel, pearled gold, anthracite).

ILLUMINAZIONI / LIGHTINGS



LIGHT
Rosso /
Red



LIGHT
Blu / Blue



LIGHT
Verde /
Green



LIGHT
Bianco /
White



ACHILLE BICOLORE /
ACHILLE BICOLOR

Tipi illuminazioni: Rosso/blu, blu/rosso, rosso/verde, bianco/blu, blu/bianco, rosso/bianco, bianco/rosso.
Lightings: Red/Blue, Blue/red, Red/green, White/blue, Blue/White, Red/white, White/red.



DEMI LIGHT

Tipi illuminazioni: Rosso leggero/rosso,
blu leggero/blu, verde leggero/verde,
bianco leggero/bianco.
Lightings: Soft red/red, soft blue/blue,
soft green/green, soft white/white.

LE FINITURE / FINISHES

INOX
Inox pallinato /
Bead blasted stainless steel



PVD
PVD oro pallinato /
Gold (pvd) bead blasted



PVD
PVD nero pallinato /
Black (pvd) bead blasted



DIMENSIONI / DIMENSIONS

