



ALPHA

Pulsante Slim con braille.
Slim push-button with braille.



FUNZIONI PRINCIPALI

- Corpo: pulsante in zama.
- Collarini: zama, (cromo o oro).
- Parte mobile: polycarbonato con superficie esterna rivestita in acciaio inox AISI 304 (possibilità di trattamento in PVD color oro o nero); cifra o decorazione in rilievo illuminabile e braille.
- Montaggio: il pulsante viene inserito frontalmente in uno scasso Ø 34,2 e fissato tramite una ghiera filettata.
- Spessore piastra: da 0,7 mm a 3 mm.
- Contatti: 1 tactile switch o 2 tactile switches.
- Cablaggio: sistemi precablati (PicoBlade o Pico-Lock).
- Illuminazione: light – rosso, bianco, blu; verde e giallo.
- Alimentazione led: 12Vo 24V DC 30mA.
- Grado di protezione: IP51.

MAIN FEATURES

- Body: zamak push button.
- Bezel: zamak, (chrome or gold)
- Pressel: polycarbonate with stainless steel AISI 304 or gold/black pvd coated finishes; raised legend(s) and braille.
- Mounting: the button is put into the cutout (Ø 34,2) from the front and fixed by threaded ring.
- Spessore piastra: da 0,7 mm a 3 mm.
- Contacts: 1or 2 tactile switches.
- Wiring: pre-wired connectors (PicoBlade o Pico-Lock).
- Lightings: light – red, white, blue, green and yellow.
- Led power supply: 12Vo 24V DC 30mA.
- Degree of protection: IP51.



DIMENSIONI / DIMENSIONS

