

Pulsanti
Push buttons



ELIOS

Pulsante da diametro 40,2 con braille.
Push button with braille, Ø 40,2.



FUNZIONI PRINCIPALI

- Struttura: pulsante in inox e nylon.
- Collarini: inox (cromo e oro).
- Parte mobile: policarbonato con superficie esterna rivestita in acciaio inox AISI 304 (possibilità di trattamento in PVD color oro o nero); cifra o decorazione in rilievo brunita e braille.
- Montaggio: il pulsante viene inserito frontalmente in uno scasso Ø 40,2 e fissato tramite una ghiera filettata.
- Spessore piastra: da 0,7 mm a 5 mm.
- Contatti: 1 micro switch o 2 micro switches.
- Cablaggio: connettori a vite o sistemi precablati (AMP, JST o minispox).
- Illuminazione: Led 12V o 24V DC 30mA.
- Corsa pulsante: 1,2 mm.
- Vita media: 2.000.000 di attivazioni.
- Grado di protezione: IP51.

MAIN FEATURES



- Body: stainless steel and nylon push button.
- Bezels: stainless/steel (chrome or gold).
- Pressel: polycarbonate with stainless steel AISI 304 or gold/black pvd coated finishes; raised legend(s) and Braille.
- Mounting: the button is put into the cutout (Ø 40,2) from the front and fixed by threaded ring.
- Faceplate Thickness: 0,7 mm to 5 mm.
- Contacts: 1 micro switch o 2 micro switches.
- Wiring: PIN or pre-wired connectors (AMP, JST or minispox).
- Illumination: Led 12V o 24V DC 30mA.
- Stroke: 1,2 mm.
- Avg. life: 2.000.000 activations.
- Degree of protection: IP51.

DIMENSIONI / DIMENSIONS

