

Display TFT TFT Display



IRIS 2.8"

Display TFT di piano 2.8".
High resolution landing display.



FUNZIONI PRINCIPALI

- Facile configurazione tramite PC.
- Aggiornamento tramite SD Card.
- Personalizzabile in sfondo, frecce, piani, logo e segnali.
- Luce di cortesia.
- Funzione stand by.
- Tastierino a bordo per le principali funzioni (volume, interfaccia, primo piano, luminosità, durata stand by).
- Comunicazione: seriale VEGA, CAN, RS485, parallela, per pilotaggio sensori magnetici.
- Case di protezione e fissaggio.
- Montaggio sia verticale che orizzontale.

Opzionale / optional



MAIN FEATURES

- Easy configuration via PC.
- Updating by SD Card.
- Customizable background, arrows, floors and signalling.
- Courtesy light.
- Energy saving system mode (stand-by).
- Easy keypad for the selection of the main features (buzzer volume, communication interface, first floor, brightness, stand-by duration).
- Communication interface: Vega serial, RS485, CAN, parallel and magnetic sensors.
- Fixing and protection case.
- Mounting: horizontal and vertical.

Iris 2.8"



SIRIO

Easy software di programmazione dedicato / Easy dedicated programming software.

Area visibile / Visible area: 56.9 x 42.5 mm.

Scasso / Cut out: 56.9 x 42.5 mm R1.9 mm.

Dimensione / Dimensions: 80 x 90 x 20 mm.

Risoluzione / Resolution: 240 (RGB) x 320-QVGA.

Pixel: 0.18 x 0 x 0.18 mm.

Colori / Colours: 65.000.

Temperatura / Temperature range: -5/+40°.

Corrente assorbita / Current consumption: 150mA.

Alimentazione / Power supply: 12/24 Vdc.

Versioni / Versions: parallela e seriale / parallel and serial.

Cablaggio / Wiring: connettori a vite e precablati / screw and pre-wiring connectors.