



Contatto a chiave
circolare / Round key
selector



Contatto a chiave quadrato /
Squared key selector

KL-KEY

Contatto a chiave luminoso.
Illuminated key selector.



FUNZIONI PRINCIPALI

- Struttura: Blocchetto chiave inserito su corpo in policarbonato con corona illuminabile.
- Collarini: ABS galvanizzati (oro o cromo), disponibile nella versione ROUND e SQUARE.
- Parte frontale: anello in acciaio e blocco chiave.
- Montaggio: il pulsante viene inserito frontalmente in uno scasso 32,2 mediante ghiera filettata.
- Spessore piastra: da 0,7 a 3 mm.
- Modelli disponibili:
 - K#2P1E (2 Posizioni , 1 estrazione);
 - K#2P2E (2 posizioni, 2 estrazioni);
 - K#1P1E (con ritorno a molla).
- Cablaggio: A fili.
- Alimentazione corona: (4XLED) 12 o 24 VDC I=20mA.
- Protezione: IP51.
- Opzionale: contatto a chiave su base VENUS XL.

MAIN FEATURES

- Body: Key block integrated in polycarbonate body with illuminated halo.
- Bezel: metallized ABS (gold or chrome); it is available in the ROUND and SQUARE version.
- Front part: Stainless Steel ring and key block.
- Mounting: it is put into the 32,2 cutout from the front and fixed by threaded ring.
- Faceplate thickness: 0,7 to 3mm.
- Available items:
 - K#2P1E (2 position/1 extraction);
 - K#2P2E (2 positions/2 extractions);
 - K#1P1E (with spring return).
- Wiring: by wires.
- Halo voltage: (4XLED) 12 or 24 VDC I=20mA
- Degree of protection: IP51.
- Optional: key block for VENUS XL model