



ERCOLE

Bouton Anti-vandale **CLASSE 2**
Vandal resistant push button **CLASS 2**.







EN 81-70

EN 81-71

WATER-PROOF

DIMENSIONS / DIMENSIONS



FONCTIONS PRINCIPALES

- Structure: bouton anti-vandale en Zamak conforme à la UNI EN 81-70 classe 2
- Finition bouton et Colerette: chrome ou or.
- Partie mobile: plastique anti-choc avec surface externe revêtue en acier inox AISI 304 (possibilité de traitement en PVD couleur or ou noir); chiffre ou décoration en relief bruni.
- Montage: le bouton est inséré de front dans un trou Ø 32,2 et fixé à l'aide d'une bague filetée.
- Épaisseur plaque: de 0,7 mm à 5 mm adapté au montage sur plaques planes.
- Contacts: 1 micro switch ou 2 micro switches.
- Câblage: bornes à vis ou systèmes précâblés (AMP ou JST).
- Éclairage: Led 12V ou 24V DC 30mA.
- Course bouton: 1,2 mm.
- Vie moyenne: 2.000.000 d'activations.
- Degré de protection: IP54.
- Finitions: inox sablé, PVD or sablé, PVD noir sablé.

MAIN FEATURES

- Body: vandal proof zamak push button in compliance with the UNI EN 81-71 standard for class 2.
- Bezels and pressel colour: chrome or gold.
- Pressel: damage free plastic with stainless steel AISI 304 or gold/black pvd coated finishes; raised legend(s).
- Mounting: the button is put into the cutout (Ø 32,2) from the front and fixed by threaded ring.
- Faceplate Thickness: 0,7 mm to 5 mm suitable for mounting on faceplates.
- Contacts: 1 micro switch or 2 micro switches.
- Wiring: PIN or pre-wired connectors (AMP, JST or minispos).
- Illumination: Led 12V or 24V DC 30mA.
- Stroke: 1,2 mm.
- Avg. life: 2.000.000 activations.
- Degree of protection: IP54.
- Finishes: blasted stainless steel, gold bead blasted, black bead blasted.

ÉCLAIRAGES / LIGHTINGS

Éclairages disponibles / Available light signals.



LIGHT
Rouge /
Red



LIGHT
Bleu /
Blue



LIGHT
Vert /
Green



LIGHT
Blanc /
White



LIGHT
Jaune /
Yellow



DEMI LIGHT

